

MATERIAL SAFETY DATA SHEET

Product name: CFR-1 Cleaner
Description: Cleaning agent for Hilti CF 120-P2, CF 120-P3 and CF-DS1 foam dispensers
Supplier: Hilti, Inc. P.O. Box 21148, Tulsa, OK 74121
Emergency # (Chem-Trec.): 1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)

INGREDIENTS AND EXPOSURE LIMITS

Ingredients:	CAS Number:	TLV:	PEL:	STEL:
Acetone	00067-64-1	750 ppm	750 ppm	1000 ppm
Isopropyl alcohol	00067-63-0	400 ppm	400 ppm	500 ppm
Butane	00106-97-8	800 ppm	800 ppm	NE
Propane	00074-98-6	NE	1000 ppm	NE

Abbreviations: PEL = OSHA Permissible Exposure Limit. TLV = ACGIH Threshold Limit Value. STEL = Short Term Exposure Limit. NE = None Established. NA = Not Applicable.

PHYSICAL DATA

Appearance:	Clear aerosol.	Odor:	Sweet pungent odor.
Vapor Density: (air = 1)	~ 2 (air = 1)	Vapor Pressure:	Not determined.
Boiling Point:	Not determined.	VOC Content:	396 g/l
Evaporation Rate:	> 3.0	Solubility in Water:	Negligible.
Specific Gravity:	0.72	pH:	Not determined.

FIRE AND EXPLOSION HAZARD DATA

Flash Point:	-4° F (-20° C)	Flammable Limits:	1.4 - 12.8%
Extinguishing Media:	Water, CO ₂ , Dry Chemical, Foam.		
Special Fire Fighting Procedures:	Contents under pressure. Cool exposed containers with water spray. A self-contained breathing apparatus (SCBA) should be used in fires involving chemicals.		
Unusual Fire and Explosion Hazards:	Extremely flammable liquid and gas under pressure. Containers can explode or be propelled through the air when exposed to extreme heat such as fire. Vapors are heavier than air and can migrate to distant ignition sources where they can be ignited. Keep away from flames or sparking equipment.		

REACTIVITY DATA

Stability:	Stable.	Hazardous Polymerization:	Will not occur.
Incompatibility:	Strong acids and oxidizing agents. Extreme heat / fire.		
Decomposition Products:	Thermal decomposition can yield CO and CO ₂ .		
Conditions to Avoid:	Exposure to high temperatures, extremely hot surfaces, flames, sparks, etc. Storage above 120° F.		

HEALTH HAZARD DATA

Known Hazards:	Acute: Skin irritation. Eye irritation and corneal burns. Central nervous system (CNS) depressant. Chronic: Dermatitis.
Signs and Symptoms of Exposure:	Eyes: Irritation and corneal burns can occur from direct contact with the eyes. Skin: Prolonged or repeated skin contact can cause irritation and defatting (drying) of the skin. Inhalation: Can be irritating to the respiratory tract if inhaled. Headaches and dizziness can occur from excessive exposure in poorly ventilated areas. Ingestion: Not a likely route of exposure. Considered to have a high acute oral toxicity based upon isopropyl alcohol content.
Routes of Exposure:	Dermal. Inhalation.
Carcinogenicity:	No ingredients are classified as a carcinogen by IARC, NTP or OSHA.
Medical Conditions Aggravated by Exposure:	Eye, skin, and respiratory conditions.

EMERGENCY AND FIRST AID PROCEDURES

Eyes:	Flush immediately with large amounts of clean water for at least 15 minutes. Seek medical attention if any effects develop.
Skin:	Wash with soap and water. Seek medical attention if any effects persist.
Inhalation:	Move victim to fresh air. Call a physician if symptoms persist.
Ingestion:	If conscious, give plenty of water to drink. Do not induce vomiting unless large amounts are ingested. Never give anything by mouth to an unconscious person. Contact a physician immediately.
Other:	Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure.

CONTROL MEASURES AND PERSONAL PROTECTIVE EQUIPMENT

Ventilation:	General (natural or mechanically induced fresh air movements).
Eye Protection:	Splash-proof chemical goggles recommended. Safety glasses with side shields as a minimum.
Skin Protection:	Gloves recommended while cleaning tools (cloth or impermeable).
Respiratory Protection:	Not normally required.

PRECAUTIONS FOR SAFE HANDLING AND USE

Handling and Storing Precautions:	Use with adequate ventilation. Extremely flammable liquid and gas under pressure. Vapors are heavier than air and can be ignited by distant ignition sources. Keep vapors and spray away from extremely hot surfaces, sparks and flame. Do not puncture or incinerate container. Do not expose to excessive heat or store at temperatures above 120° F (49° C). Avoid contact with eyes, skin and clothing. Practice good hygiene; i.e. wash after using and before eating or smoking. Store indoors out of direct sunlight. For industrial use only. Keep out of reach of children. Storage classifications: NFPA = Level 3; OSHA = Class 1A.
Spill Procedures:	Remove all sources of ignition. Take up with an absorbent material and place in a container for proper disposal in accordance with all applicable local, state, or federal requirements.

REGULATORY INFORMATION

Hazard Communication:	This MSDS has been prepared in accordance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.
HMIS Codes:	Health 1, Flammability 3, Reactivity 0, PPE A (Goggles)
DOT Shipping Name:	Consumer commodity, ORM-D
IATA/CAO Shipping Name:	Aerosols, flammable, n.o.s. Class 2.1, UN 1950, Ltd. Qty.
TSCA Inventory Status:	Chemical components listed on TSCA inventory.
SARA Title III, Section 313:	This product does not contain any ingredients which are subject to reporting under Section 313 of SARA Title III (40 CFR Part 372).
EPA Waste Code(s):	D001
Waste Disposal Methods:	Consult with regulatory agencies or your corporate personnel for disposal methods that comply with local, state, and federal safety, health and environmental regulations.

CONTACTS

Customer Service:	1 800 879 8000	Technical Service:	1 800 879 8000
Health / Safety:	1 800 879 6000	Jerry Metcalf	(x6704)
Emergency # (Chem-Trec):	1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)		

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.